

Network System for Image Data

Background of the Invention

1. Field of the Invention

5 The present invention relates to a network system for image data processing systems, in which image data is shared between a plurality of image processing systems.

2. Description of the Related Art

10 Networks for image data processing systems are known that use standard distribution protocols, such Ethernet, TCP/IP and HiPPI. In video facilities houses, video data is often conveyed between machines using digital video tape or similar magnetic storage media. This provides a relatively inexpensive way of conveying data between stations and is beneficial particularly when image data is to be archived. It is also satisfactory if image
15 data processing is to be performed at a single station, whereafter the material will often leave the facility house altogether.

 A recent trend has been towards having a plurality of different stations within a facilities house therefore it has been appreciated that highly powered
20 stations, having relatively high hourly charges, may be used for specific operations where a high degree of processing power is required. However, overall charges may be reduced by performing less demanding tasks at more modest stations. However, a problem with this approach is that the data must be transferred from one station to another and the act of transferring data,
25 with its inherent time requirement, may off-set any gains made by using less expensive stations to perform particular tasks.

 As previously stated, it is known to convey video image data over

internal networks but given known approaches, high bandwidth networks, such as HiPPI, are relatively expensive, which again off-sets any financial advantage made from transferring data between stations. Alternatively, it is known to convey data over TCP/IP networks but under these circumstances the rate of data transfer is relatively low, whereas the amount of data required to be transferred is usually relatively high, particularly when manipulating high bandwidth images, such as high definition TV (HDTV). Increasingly, in video facilities houses, HDTV images and images of even higher bandwidth, are being manipulated, particularly when source material is obtained by scanning cinematographic film.

Thus, in order to make best use of available hardware, it is preferable to transfer data over networks, preferably by making storage devices accessible to a plurality of stations. However, a problem arises in that known techniques will often off-set any commercial advantages gained from an ability to transfer data between stations.

Brief Summary of the Invention

According to an aspect of the present invention, there is provided a networked image data processing environment, comprising a plurality of image data processing systems; a plurality of data storage systems, wherein each of said data storage systems is operated under the direct control of one of said image processing systems; a high bandwidth switching means connected to each of said data processing systems; a low bandwidth network connected to said image processing systems and to said switching means, by which one of said processing systems controls the operation of said switching means and in which a first processing system requests access to a data storage system controlled by a second processing system over said low

bandwidth network; said second processing system makes an identification of storage regions that may be accessed by said first processing system; said second processing system conveys said identification to said first processing system over said low bandwidth network; and said first processing system accesses said identified storage portion via said high bandwidth switching means.

Brief Description of the Several Views of the Drawings

Figure 1 shows an image data processing system;

10 *Figure 2* illustrates image frames of the type processed by the system shown in *Figure 1*;

Figure 3 illustrates a redundant array of inexpensive disks accessed by a fibre channel interface;

15 *Figure 4* illustrates a known network configuration connecting systems of the type shown in *Figure 1*;

Figure 5 shows a networked image data processing environment embodying the present invention;

Figure 6 shows a request thread executed by a requesting processor;

20 *Figure 7* illustrates a data request demon executed by a supplying processor;

Figure 8 shows an alternative network environment embodying the present invention;

Figure 9 illustrates an off-line processing system of the type shown in *Figure 8*; and

25 *Figure 10* illustrates a high definition image processing system of the type shown in *Figure 8*.

Best Mode for Carrying Out the Invention

An image data processing system is illustrated in *Figure 1* consisting of a silicon graphics octane computer **101** configured to receive manual input signals from manual input devices **102** (such as a keyboard, mouse, stylus and touch tablet etc) and is arranged to supply output signals to a display monitor **103**. Operating instructions are loaded into the octane computer **101**, and thereafter stored on a local disk, via a data carrying medium, such as a CD ROM **104** receivable within a CD ROM reader **105**. Program instructions are stored locally within the octane **101** but frames of image data are stored on a RAID (Redundant Array of Inexpensive Disks) system via a fibre channel interface **106**. RAID calculations are performed by the octane **101** and data values are addressed so as to effect striping of image frames over the disk array.

A plurality of video image frames **201, 202, 203, 204** etc are illustrated in *Figure 2*. Each frame in the clip has a unique frame identification (frame ID) such that, in a system containing many clips, each frame may be uniquely identified. In a system operating with standard broadcast quality images, each frame consumes approximately one megabyte of data. Thus, by conventional computing standards, frames are relatively large therefore even on a relatively large disk array, the total number of frames that may be stored is ultimately limited. However, an advantage of this situation is that it is not necessary to establish a sophisticated directory system thereby assisting in terms of frame identification and access.

As octane **101** boots up, it mounts its associated file system and takes control of data stored at the beginning of the storage device

describing object allocation for the file system in an area referred to as a superblock. The superblock describes the frames that are available within the file system and in particular maps frame ID's (identifications) to physical storage locations within the disk system. Thus, as illustrated in *Figure 2*, frame ID101 is stored at location **101**, frame ID102 is at location **102** and frame ID103 is at location **103** etc. Thus, if an application identifies a particular frame, it is possible for the system to convert this to a physical location within disk storage.

Fibre channel interface **106** communicates with a redundant array of disks **301** as illustrated in *Figure 3*. The array **301** includes six physical hard disk drives, illustrated diagrammatically as drives **310**, **311**, **312**, **313** and **314**. In addition to these five disks, configured to receive image data, a sixth redundant disk **315** is provided.

An image field **317**, stored in a buffer within memory, is divided into five stripes, identified as stripe zero, stripe one, stripe two, stripe three and stripe four. The addressing of data from these stripes occurs using similar address values with multiples of an off-set value applied to each individual stripe. Thus, while data is being read from stripe zero, similar address values read data from stripe one but with a unity off-set. Similarly, the same address values are used to read data from stripe two with a two unit off-set, with stripe three having a three unit off-set and stripe four having a four unit off-set. In a system having many storage devices of this type and with data being transferred between storage devices, a similar striping off-set is used on each system.

As similar data locations are being addressed within each stripe, the resulting data read from the stripes is XOR'd together by process **318**, resulting in redundant parity data being written to the sixth drive **315**. Thus,

as is well known in the art, if any of disk drives **310** to **315** should fail, it is possible to reconstitute the missing data by performing a XOR operation upon the remaining data. Thus, in the configuration shown in *Figure 3*, it is possible for a damaged disk to be removed, replaced by a new disk and the missing data to be re-established by the XORing process. Such a procedure for the reconstitution of data in this way is usually referred to as disk healing.

Systems of the type shown in *Figure 1* may be connected together via network configuration as shown in *Figure 4*. Each image data processing system **401**, **402**, **403** and **404** is substantially similar to the system shown in *Figure 1*. Each communicates with a respective disk array **411**, **412**, **413**, **414** over a respective fibre channel **431**, **432**, **433**, **434**. As shown in *Figure 1*, each system, such as system **401** includes an octane processor **441**, input devices **442** and a monitor **443**.

Each processor, such as processor **441**, includes a network card to facilitate network communication over an Ethernet network **445**. A program facilitating network communication remains resident on each processing system **441** enabling systems to respond to requests made from other systems. In this way, it is possible for system **401**, for example, to receive image data from, for example, disk storage array **413**. To achieve this, processor **441** makes a request over network **445** to the processor of system **403**. A demon running on system **403** catches this request and locally determines whether it is possible for the image data to be supplied to system **401**. If it is possible to supply the data, the data is read from disk storage **413** locally to system **403** and then transmitted over the Ethernet **445** to system **401**. At system **401**, the data may be buffered locally to storage **411** whereafter manipulations may be performed upon the data in real-time.

However, it should be appreciated that the transfer of data over Ethernet **445** occurs at a rate substantially less than real-time.

It is possible to install higher bandwidth networks but these are expensive and tend not to be deployed. If a large amount of data is to be transferred, it may be preferable to store the data onto removable media, such as magnetic tape and thereafter physically transfer it to another station. However, this does require duplication of the data and procedures must be effected to ensure that the most up to date versions of material may be identified and accessed.

A networked image data processing environment embodying the present invention is illustrated in *Figure 5*. The embodiment includes eight image data processing systems **501, 502, 503, 504, 505, 506, 507, 508** each having a respective disk array storage system **511, 512, 513, 514, 515, 516, 517** and **518**. Each of the image data processing systems **501** to **508** is substantially similar to image data processing system **401** etc shown in *Figure 4*. Each of the data storage systems is operated under the direct control of its respective image processing system. Thus, data storage system **511** is operated under the direct control of data processing system **501**. In this respect, data processing system **501** behaves in a substantially similar manner to data processing system **401** and data storage system **511** behaves in a substantially similar manner to storage system **411**. For example, each storage system **511** to **518** may be of the type obtainable from the present Assignee under the trademark "STONE" providing sixteen disks each having nine Gigabytes of storage.

The environment includes a sixteen port non-blocking fibre channel switch type **521**, such as the type made available under the trademarks "VIXEL" or "ENCORE". Switches of this type are known for providing high

bandwidth access to file serving systems but in the present embodiment, the switch has been employed within the data processing environment to allow full bandwidth accessibility between each host processor **501** to **508** and each storage system **511** to **518**. Each data processing system **501** to **508** is connected to the fibre channel switch by a respective fibre channel **531** to **538**. Similarly, each storage system is connected to the fibre channel switch via a respective fibre channel **541** to **548**. In addition, an Ethernet network **551**, substantially similar to network **445** of *Figure 4*, allows communication between the data processing systems **501** to **508** and the fibre channel switch **521**.

Within the environment, a single processing system, such as system **501**, is selected as channel switch master. Under these conditions, it is not necessary for all of the processing systems to be operational but the master system **501** must be operational before communication can take place through the switch. However, in most operational environments, all of the processing systems would remain operational unless taken off-line for maintenance or upgrade etc. Master processor **501** communicates with the fibre channel switch **521** over the Ethernet network **551**. Commands issued by processor **501** to the fibre channel switch define physical switch connections between processing systems and the disk storage arrays **511** to **518**.

On start-up, the switch **521** is placed in a default condition to the effect that each processor is connected through the switch **521** to its respective storage system. Thus, on booting up processing system **502**, for example, it mounts its own respective storage system **512** and takes control of the superblock defining the position of images held on that storage system, as illustrated in *Figure 2*. Thus, each processing system **501** to **508** takes control

of its respective data storage system such that each storage system **511** to **518** runs under the control of its respective host. Thus, another processing system, such as system **507**, may only gain access to storage system **512** if it is allowed to do so by its host data processing system **502**.

5 It is not possible for data processing system **507** to mount the superblock of storage system **512** or any of the other storage systems with the exception of its own storage system **517**. In theory, this could be possible but the procedures operated by the data processing systems are configured so as to prevent this, thereby maintaining data integrity.

10 A request to gain access to an alternative data storage system is made over Ethernet connection **511**. Again, a demon runs on each of the processing systems in order to respond to these requests and the procedures formed are substantially similar to the procedures executed by the environment described with respect to *Figure 4*. Thus, data processing
15 system **507** may issue a request over Ethernet **551** to data processing system **502** to the effect that processor **507** requires access to storage system **512**, that is primarily under control of data processing system **502**.

 Within the previous environment, processes executed by data processing system **502** and system **507** could effect a direct memory access
20 to processing system **507** over Ethernet **551** but, as previously stated, this would not occur in real-time (that is, at video display rate). However, in the present embodiment, once it has been established that processor **507** may modify particular frames stored on storage system **502**, processor **502** makes a request to control processor **501** which in turn effects a modification to the
25 fibre channel switch **521**. The non-blocking switch **521** provides a full bandwidth fibre channel between fibre channel interface **542** and fibre channel interface **537**.

By providing full bandwidth access to the storage system of other hosts, substantial advantages are gained in terms of a reduction of data copying and transfer and an ability to process data stored elsewhere in a fashion similar to the processing of local data. Thus, with full bandwidth
 5 access provided by the fibre channel switch **521**, it is possible to perform real-time effects, previously only implemented using local storage, while accessing remote data again providing significant time savings and storage optimisations.

An example has been described in which processor **507**, a host to storage system **517**, requests frames of data from storage system **512**,
 10 hosted by processing system **502**. Processing system **502** retains control of storage system **512** therefore in order for processing system **507** to gain access to storage system **502**, it is necessary for procedures to be executed, in the form of a request thread, on processor **507** and for procedures, in the form of a response demon, to be executed on processor **502**.
 15

A request thread, executed by processor **507** in the example but generally executable by all processors in the environment, is detailed in *Figure 6*. A thread is initiated at step **601** whereafter at step **602** a frame identification for the remote data required is identified. Thereafter, at step **603**
 20 the host processor responsible for this data is identified which, in this example, is host processor **502**.

At step **604** a request is made by host processor **507** over Ethernet connection **551** to host processor **502**. This request includes data receivable by processor **502** to the effect that host processor **507** requires access to specific frames held on storage system **512**.
 25

In response to this request, host processor **502** may allow processor **507** to access storage system **512** through the fibre channel switch **521**.

Alternatively, processor **502** may require full bandwidth access to storage system **512** itself and under these circumstances it may refuse to give processor **507** access to its storage system. Thus, at processor **507** a question is asked as to whether the remote host (**502** in this example) will release access to its disk system (system **512** in this example). If the question is answered in the negative, a question is asked at step **606** as to whether a further request is to be made in an attempt to gain access and if this is answered in the affirmative, control is returned to step **604**. The system would be programmed to make several attempts and the actual number of attempts made before no further attempts are made is a detail of implementation. If it is decided that no further attempts will be made, control is directed to step **612** where the thread ends.

If the remote host processor is prepared to give access to its disk storage system, the question asked at step **605** will be answered in the affirmative and control will be directed to step **607**.

The requesting processor **507** supplies a frame identification or identifications for a plurality of frames making up a continuous clip. Thus, for example, processor **507** may submit a request to processor **502**, over Ethernet connection **551**, to the effect that it requires access to frames with frame ID's ID101 to ID105, as shown in *Figure 2*. Host processor **502** then consults the superblock of its mounted storage system **512** to determine that frame ID101 is at location LOC101, and so on until frame identification ID105 which is located at location LOC105. This information is then returned back to the requesting processor **507**, as shown at step **607** to the effect that details of the storage location have been received.

At step **607** processor **507** issues a request to the effect that a storage switchover is required. This request is made via control processor **501** which

in turn issues a command to fibre channel switch **521** resulting in a disconnection of storage system **512** to processing system **502** and a connection of storage system **542** to the requesting host processing system **507**. With this connection in place, processing system **507** theoretically has full access at full bandwidth to storage system **512**. However, instructions executed by processing system **507** are such that, although processing system **507** has full bandwidth access to storage system **512**, it is only permitted to modify frames that constitute part of the original request. Thus, processing system **507** may access locations LOC101, LOC102, LOC103, LOC104 and LOC105 in this particular example but it is not permitted to access any other positions within disk storage system **512**.

At step **610** a question is asked as to whether the access has completed and if answered in the negative control is returned to step **609** thereby permitting further access at full bandwidth. Various tests may be included within step **610** to determine when the transfer should be completed. Preferably, full bandwidth access to storage systems should be returned to their host processors as soon as possible and only switched over to other processors when specific data transfers are required.

When the question asked at step **610** is answered in the affirmative, an acknowledgement of completion is issued by processor **507** to processor **502** and processor **501** at step **611**, resulting in switch **521** being activated to reconnect storage system **512** with its host processor **502** and also instructing processor **502** to the effect that the switchover has taken place. Consequently, processing system **502** may now take full control of its associated disk storage system **512**. Thereafter, the thread ends at step **612**.

The data request demon executed by each of the processing systems **501** to **508** is detailed in *Figure 7*. As is known with technology of this type,

the program remains resident but not executing until called upon to do so by an external request. The residency of the thread is illustrated by step **701**.

The process is initiated at step **702** upon receiving an interrupt to the effect that a data access is required. At step **703** a question is asked as to whether access can be given and if answered in the negative, an instruction to the effect that access is not available is returned to the requesting processor over Ethernet **551**. Thus, following the previous example, processor **502** will deny access to processor **507** if processor **502** requires full bandwidth access to its own local storage system **512**. Alternatively, if full bandwidth access is not required, it may be possible to allow the requesting processor (processor **507**) to gain access through the fibre channel switch **521**. If access is not available, the thread terminates and stays resident at step **705** returning it to the resident state **701**.

If access can be given the question asked at step **703** is answered in the affirmative and control is directed to step **706**. The requesting host generates a frame identification and the requested identification is identified at step **706**. The processor then makes reference to its superblock allowing it to return details of storage locations at step **707**.

After returning the storage locations, the host processor effectively hands over access to its local disk storage system. The philosophy of procedures executed by the host system is that other hosts should not be allowed access for long. Consequently, at step **708** a question is asked as to whether access has been returned, implemented by a completion acknowledgement generated at step **611**. If access has not been returned, the question asked at step **708** is answered in the negative and a question is asked at step **709** as to whether a call should be made to actively request return of the access. If this question is answered in the negative, control is

returned to step **708**.

If the local processor determines that another host processor has retained access for too long, resulting in the question asked at step **709** being answered in the affirmative, a request is issued at step **710** for the return of disk access. This should then result in access being returned whereafter the demon may terminate and stay resident.

Ideally, host processors should allow other processors access for periods allowing them to do useful work therefore under ideal conditions access should be returned before the host processor demands it, resulting in the question asked at step **708** being answered in the affirmative. This results in control being returned to the local processor and again the thread terminates at step **711**.

In the network environment shown in *Figure 5*, all of the processing systems **501** to **508** are substantially similar and are implemented on the Silicon Graphics Octane platform. Manipulations upon image data, using software applications such "FLAME" and "FIRE" licensed by the present Assignee, may be executed to perform manipulations upon standard bandwidth video material. However, in many environments, higher bandwidth images are processed, such as those for high definition television or for those generated by scanning cinematographic film. Similarly, stations of lower capability are also provided, possibly for manipulating lower bandwidth material, off-line editing or for performing simple manipulations upon data, possibly loading data into the environment from video tape.

An alternative environment is illustrated in *Figure 8*. Fibre channel switch **801** is substantially similar to switch **521** and storage system **802** to **809** are substantially similar to systems **511** to **518**.

Storage systems **802** to **809** are connected to fibre channel switch **801**

over respective fibre channel interfaces **812** to **819**. These are substantially similar to interfaces **541** to **548** and result in a further eight interface nodes being available on switch for communication to processing systems. Four interface nodes of the fibre channel switch **801** are connected by interfaces **821** to a Silicon Graphics Onyx2 computer **822**. These four fibre channel communications are connected, by default, to storage system **802** to **805**. This provides full bandwidth transfer of high definition television signals between storage and the Onyx2 computer or it provides several full bandwidth channels of lower definition signals, such as standard broadcast video. This represents top-end image processing capability but, as such, would incur substantial time charges within a facilities house.

In known environments employing top-end equipment, it is known that time may be taken on the equipment merely to load source material into the environment or to download completed material from the environment. Under these circumstances, many of the capabilities of the top-end facility effectively becomes redundant and is thereby a substantial overhead.

In the environment shown in *Figure 8*, Onyx2 computer **822** acts as switch master and as such allows the Onyx2 to perform a reconnection such that interfaces **821** are connected to storage systems **806** to **809** instead of being connected to storage systems **802** to **805**. An advantage of performing a switchover of this type is that while the Onyx2 computer **822** is performing top-end operations using data stored in storage systems **802** to **805**, data may be removed from storage systems **806** to **809** and new material may be loaded to these storage systems. Eventually, a particular job will complete and finished material will reside on storage systems **802** to **805**. It is now necessary to remove the data from these storage systems but this is a relatively lowly task to be performed on the Onyx computer. Consequently, a

switchover occurs such that the Onyx2 computer may now manipulate material stored on systems **806** to **809**. The transfer of completed data from storage systems **802** to **805** and its replacement with new source material is performed by an alternative system.

5 In addition to Onyx2 computer **822**, an octane-based system **824** is connected to the fibre channel switch **801** via an interface **826**. Onyx system **822** and octane system **824** communicate with the fibre channel switch **801** over an Ethernet network **827**. Octane system **824** is substantially similar to the data processing system shown in *Figure 5*, with the addition of a second
10 Ethernet network **828**. This in turn has four off-line systems **831**, **832**, **833** and **834** connected thereto. The off-line systems are primarily configured to facilitate the loading of video information such that this loaded information may then be manipulated by the Onyx2 system in real-time. In addition, modest housekeeping manipulations may be performed by systems **831** to
15 **834** and these systems may also be configured to perform off-line editing procedures upon compressed representations of video frames.

Thus, in the environment shown in *Figure 8*, any of systems **824**, **831** to **834** may be involved with the transfer of data to the storage systems **802** to **809**. In a preferred arrangement, the Onyx2 system **822** remains almost
20 constantly in operation and is given access to sub-set **802** to **805** of the storage systems or to sub-set **806** to **809** of the storage systems. When using storage systems **802** to **805**, storage systems **806** to **809** may be accessed by the secondary system **824** or by the tertiary systems **831** to **834**. Off-line station **831** may be allocated the task of ensuring that the Onyx2
25 system **822** is kept busy such that while working on a sub-set of disks an off-line operator at station **831** must ensure that data is maintained in the complimentary sub-set of disks. In this way, a handover may occur

whereafter the off-line operation at station **831** would be responsible for releasing process data and the loading of new data to ensure that a further handover could take place and so on thereby optimising availability of the Onyx2 system.

5 Off-line processing system **831** is detailed in *Figure 9*. New input material is loaded via a high definition video recorder **901**. Operation of recorder **901** is controlled by a computer system **902**, possibly based around a personal computer (PC) platform. In addition to facilitating the loading of high definition images to storage systems, processor **902** may also be
10 configured to generate proxy images, allowing video clips to be displayed via a monitor **903**. Off-line editing manipulations may be performed using these proxy images, along with other basic editing operations. An off-line editor controls operations via manual input devices including a keyboard **904** and mouse **905**.

15 Data processing system **822** is illustrated in *Figure 10*, based around an Onyx2 computer **1001**. Program instructions executable within the Onyx2 computer **1001** may be supplied to said computer via a data carrying medium, such as a CD ROM **1002**.

20 Image data may be loaded locally and recorded locally via a local digital video tape recorder **1003** but preferably the transferring of data of this type is performed off-line, using stations **831** to **834** etc.

 An on-line editor is provided with a visual display unit **1004** and a high quality broadcast quality monitor **1005**. Input commands are generated via a stylus **1006** applied to a touch table **1007** and input commands may also be
25 generated via a keyboard **1008**.

 The environment described herein allows a plurality of disk storage systems to be accessed by a plurality of host processors at full bandwidth.

Furthermore, the procedures for effecting a handover via a full bandwidth switch ensure that the integrity of data contained within the system is maintained. In particular, a host processor retains control of a particular disk system and requests must be made to the host processor in order for a remote processor to gain access thereto.

5

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000